

ATF 2000 DEX II

Description

Lubricant for automatic transmission gearboxes requesting a Dexron II quality level, clutches and steering systems in passenger cars, commercial trucks and off-road machinery.

Application

ATF 2000 DEX II is suitable for automatic transmissions, torque converters, power steering, power transmission systems, power steering cars, industrial and hydraulic clutches. Reduction of friction. It offers optimal operation of the torque converter. Wide operating temperature range.

Operation Characteristics

- Protection of metal parts against corrosion
- Excellent wear protection
- Excellent performance at low and high temperatures
- Excellent anticorrosion and antirust properties

Specifications, Approvals, Recommendations

GM DEXRON II D, ALLISON C-4, CAT TO-2, VOITH, MB 236.7, RENK, ZF-TE-ML 09/11/14, MAN 339-D

Typical Physical Characteristics

	ASTM	DEX II
SPECIFIC GRAVITY (kg/lt)	D 1298	0,856
VISCOSITY AT 40°C (cSt)	D 445	36
VISCOSITY AT 100°C (cSt)	D 445	7,3
VISCOSITY INDEX	D 2270	170
FLASH POINT (°C) min.	D 92	220
POUR POINT (°C)	D 97	>-40
COLOUR		RED

These are typical values. Small variation should be expected for future productions / blendings

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.