

CHROME FE 0W20

Description

Ultra fuel economy synthetic engine oil formulated with excellent performance synthetic base stocks and a precisely balanced component additive system. It offers maximum protection in severe climate and driving conditions. Increased engine efficiency and improved fuel economy.

Application

ROVEL CHROME FE SAE 0W-20 is designed for passenger cars and light commercial vehicles with extended drain intervals. Specially developed for energy conserving gasoline engines. Ultimate cold starting performance. Fuel economy. Minimum exhaust emissions and maximum engine protection.

Operation Characteristics

- Low viscosity advanced full synthetic formula
- Outstanding thermal and oxidation stability
- Outstanding low temperature capabilities
- Excellent resistance to oil degradation
- Unsurpassed wear and sludge protection
- Enhanced fuel economy with a corresponding reduction in emissions
- Low oil consumption for less frequent top -up

Specifications, Approvals, Recommendations

API SN-RC, ILSC GF-5, GM Dexos 1.

Typical Physical Characteristics

	ASTM	0W-20
DENSITY (kg/lit)	D 1298	0,849
VISCOSITY AT 40°C (cSt)	D 445	46,2
VISCOSITY AT 100°C (cSt)	D 445	8,6
VISCOSITY INDEX	D 2270	167
FLASH POINT (°C) min.	D 92	220
POUR POINT (°C)	D 97	-45
TBN mg KOH /g	D 2896	8,3
CCS @ -35° C max	D-5293	6200

These are typical values. Small variation should be expected for future productions / blendings

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.