

CHROME FS 5W30

Description

High performance, full SAPS, synthetic engine oil for passenger cars and light commercial vehicles offering optimum anti wear protection and engine cleansing for extended oil drain intervals.

Application

ROVEL Chrome FS 5W-30 is an advanced, full SAPS synthetic lubricant, designed for gasoline and diesel engines of passenger cars and light trucks without DPF. It is suitable for those vehicles that use LPG or CNG type fuels. It offers fuel economy and reduced emissions.

Operation Characteristics

- Excellent dispersancy of combustion residues
- Excellent anti-wear protection
- Reduced fuel consumption and reduced emissions
- Minimum oil consumption because it remains in the classification (grade) regardless of the operating conditions
- Compatible with all gaskets and sealants

Specifications, Approvals, Recommendations

API SL/CF, ACEA A3/B4, MB 229.3, VW 501.01/502.00/505.00, BMW LL-01, OPEL GM-LL-B-025.

Typical Physical Characteristics

	ASTM	5W-30
SPECIFIC GRAVITY (kg/l)	D 1298	0,862
VISCOSITY AT 40°C (cSt)	D 445	68,1
VISCOSITY AT 100°C (cSt)	D 445	11,8
VISCOSITY INDEX	D 2270	169
TBN	D 2896	10,5
FLASH POINT (°C) min.	D 92	230
POUR POINT (°C)	D 97	-36

These are typical values. Small variation should be expected for future productions / blendings.

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.