

RACE GT2 10W60

Description

Super high-performance synthetic oil for racing and modified engine cars. It offers ultimate wear and sludge protection under extreme performance and racing conditions. It exhibits excellent oxidation resistance at high temperatures and keeps the engine clear.

Application

ROVEL Race GT2 10W-60 is an advanced lubricant specially designed for the lubrication of all modern racing engines operating under severe conditions, where temperature and speed are paramount.

Operation Characteristics

- Reliable operation and efficiency in all modern engines
- Protection against creating combustion residues
- Extended engine life
- Excellent oxidation and thermal stability

Specifications, Approvals, Recommendations

API SN, ACEA A3/B4

Typical Physical Characteristics

	ASTM	10W-60
SPECIFIC GRAVITY (kg/l)	D 1298	0,855
VISCOSITY AT 40°C (cSt)	D 445	154
VISCOSITY AT 100°C (cSt)	D 445	23
VISCOSITY INDEX	D 2270	179
FLASH POINT (°C) min.	D 92	230
POUR POINT (°C)	D 97	-40

These are typical values. Small variation should be expected for future productions / blendings.

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.