

SILVER LX 20W50

Description

High performance multi grade engine oil for passenger cars and light trucks. Cleans the engine. Protects against wear. Reduces noise. Reduces the cost of oil change.

Application

It is an advanced mineral lubricant, designed for gasoline and diesel engines of passenger cars and light trucks. It is very efficient in hot climatic conditions.

Operation Characteristics

- Reliable performance even in the toughest conditions.
- Excellent cold starting and rapid oil circulation.
- Excellent protection against wear and excellent lubrication.
Excellent dispersancy and deposit control.
- Compatible with all gaskets and sealants.
- Totally minimum oil consumption.

Specifications, Approvals, Recommendations

API SL/ CF

Typical Physical Characteristics

	ASTM	20W50
DENSITY (kg/lt)	D 1298	0,892
VISCOSITY AT 40°C (cSt)	D 445	154,5
VISCOSITY AT 100°C (cSt)	D 445	18,5
VISCOSITY INDEX	D 2270	135
FLASH POINT (°C) min.	D 92	240
POUR POINT (°C)	D-97	8,5
TBN	D 2896	-24

These are typical values. Small variation should be expected for future productions / blendings

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.