

MARINA 4T FCW 10W40

Description

High performance lubricant, designed for 4-stroke outboard marine engines.

Application

MARINA 4T FCW 10W-40 is a versatile synthetic lubricant specially designed for the new generation of four-stroke outboard engines. It offers excellent anti-corrosion protection in extreme conditions of the marine environment and high protection against damage at low and high speeds.

Operation Characteristics

- Minimizes the possibility of welding the piston rings
- Efficient operation of the engine
- Protects combustion chamber from deposits, rust and corrosion
- Reduced emissions and reduced fuel consumption

Specifications, Approvals, Recommendations

API SG, NMMA:FC-W

Typical Physical Characteristics

	ASTM	MARINE 4T FCW 10W-40
SPECIFIC GRAVITY (kg/lit)	D 1298	0,871
VISCOSITY AT 40°C (cSt)	D 445	93
VISCOSITY AT 100°C (cSt)	D 445	14,2
VISCOSITY INDEX	D 2270	157
FLASH POINT (°C) min.	D 92	220
POUR POINT (°C)	D 97	-33

These are typical values. Small variation should be expected for future productions / blendings.

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.