

TURBO CHARGE 15W40

Description

High quality multi grade HDD engine oils designed to offer protection and engine cleanliness in older vehicles operating under normal conditions.

Application

TURBO CHARGE 15W40 is suitable for all engines (simple and TURBO) of gasoline passenger trucks, buses, taxis and industrial machinery. Recommended for mixed fleets.

Operation Characteristics

- Protection of metal parts against corrosion and rust
- Resistance to oxidation at high temperatures
- Excellent dispersion of lubricant on metal surfaces
- Protection against creating combustion residues
- Excellent performance at low temperatures
- Excellent detergency

Specifications, Approvals, Recommendations

API CH-4/SJ, ACEA E5-02 (quality), ACEA A3/B3, MAN M 3275-1, MB 228.3, VOLVO VDS-2 (quality), MTU Cat.2

Typical Physical Characteristics

	ASTM	15W-40
SPECIFIC GRAVITY (kg/lit)	D 1298	0,884
VISCOSITY AT 40°C (cSt)	D 445	108
VISCOSITY AT 100°C (cSt)	D 445	14
VISCOSITY INDEX	D 2270	130
FLASH POINT (°C) min.	D 92	230
POUR POINT (°C)	D 97	-24
TBN	D 2896	9

These are typical values. Small variation should be expected for future productions / blendings.

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.