

GOLD XR 10W40

Description

High performance semi-synthetic engine oil for passenger cars and light commercial vehicles. It offers optimum anti wear protection and engine cleansing for long drain intervals.

Application

ROVELGOLD XR 10W-40 is an advanced lubricant designed for wear protection. Recommended for meeting the high demands of medium and high speed, direct injection diesel and gasoline engines and is also suitable for dual fuel CNG/LPG engines.

Operation Characteristics

- Reliable operation and engine efficiency.
- Excellent dispersancy of combustion residues.
- Excellent cold starting and rapid oil circulation to minimize engine wear.
- Reduced fuel consumption and reduced emissions
- High anti-oxidation protection.
- Compatible with all gaskets and sealants
- Low oil consumption.

Specifications, Approvals, Recommendations

API SN/CF, ACEA A3/B4, MB 229.3, VW 501.01/505,00, BMW LL-01, PSA B71 2300, RENAULT RN 0700/0710

Typical Physical Characteristics

	ASTM	10W-40
SPECIFIC GRAVITY (kg/lit)	D 1298	0,870
VISCOSITY AT 40°C (cSt)	D 445	97,5
VISCOSITY AT 100°C (cSt)	D 445	14,5
VISCOSITY INDEX	D 2270	155
TBN	D 2896	11
FLASH POINT (°C) min.	D 92	220
POUR POINT (°C)	D 97	-36

These are typical values. Small variation should be expected for future productions / blendings.

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.