

# ACTRO 5 20W50

## Description

High quality, multi-grade HDD engine lubricant for use in older diesel and gasoline engines.

## Application

It is an advanced lubricant designed to offer protection and engine cleanliness in normally aspirated and turbo-charged engines of older vehicles operating under normal conditions.

## Operation Characteristics

- Reliable operation and efficiency.
- High viscosity index.
- Protection against wear.
- Very good detergent properties.
- Compatible with all gaskets and sealants.
- Very good low temperature performance.

## Specifications, Approvals, Recommendations

API CF-4/SJ

## Typical Physical Characteristics

	<b>ASTM</b>	<b>20W-50</b>
<b>DENSITY (kg/l)</b>	D 1298	0,887
<b>VISCOSITY AT 40°C (cSt)</b>	D 445	158
<b>VISCOSITY AT 100°C (cSt)</b>	D 445	18,2
<b>VISCOSITY INDEX</b>	D 2270	128
<b>FLASH POINT (°C ) min.</b>	D 92	225
<b>POUR POINT (°C)</b>	D 97	-27
<b>CCS @ -15 C</b>	D-5293	6900

*These are typical values. Small variation should be expected for future productions / blendings*

## Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.