

# GOLD AR 10W40

## Description

Semi-synthetic engine oil for passenger cars and light trucks. Cleans the engine. Protects against wear. Reduces noise. Reduces the cost of oil change.

## Application

It is an advanced lubricant designed for modern passenger cars, and light trucks equipped with petrol or diesel engines. It is suitable for all seasons.

## Operation Characteristics

- Reliable performance even in the toughest conditions.
- Excellent cold starting and rapid oil circulation.
- Excellent protection against wear and excellent lubrication. Excellent dispersancy and deposit control.
- Compatible with all gaskets and sealants.
- Totally minimum oil consumption.

## Specifications, Approvals, Recommendations

API SL/ CF

## Typical Physical Characteristics

	ASTM	10W-40
DENSITY (kg/ltr)	D 1298	0,871
VISCOSITY AT 40°C (cSt)	D 445	96,5
VISCOSITY AT 100°C (cSt)	D 445	14,5
VISCOSITY INDEX	D 2270	156
FLASH POINT (°C ) min.	D 92	220
POUR POINT (°C)	D 97	-33
TBN	D 2896	9
CCS @ -25 C	D-5293	5950

*These are typical values. Small variation should be expected for future productions / blendings*

## Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.