

MARINA Gear 80W90

Description

Synthetic base lubricant for gearboxes of inboard and outboard marine engines.

Application

High performance, extreme pressure, multi-grade gear oil designed for the gear boxes and stern drives of outboard and inboard engines. It offers excellent sea water corrosion resistance, load carrying performance and anti-wear protection.

Operation Characteristics

- Protection of metal parts from rust and corrosion even with the presence of water.
- Excellent operation in extreme conditions due to the special additives it contains.
- Excellent dispersion of the lubricant on metal surfaces.

Specifications, Approvals, Recommendations

API GL-5

Typical Physical Characteristics

	ASTM	MARINA GEAR 80W-90
SPECIFIC GRAVITY (kg/lit)	D 1298	0,895
VISCOSITY AT 40°C (cSt)	D 445	133
VISCOSITY AT 100°C (cSt)	D 445	15
VISCOSITY INDEX	D 2270	116
FLASH POINT (°C) min.	D 92	220
POUR POINT (°C)	D 97	-30

These are typical values. Small variation should be expected for future productions / blendings.

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.