

# MOTO MIX 2T

## Description

Mineral two-stroke engine lubricant for low performance and low capacity engines.

## Application

ROVEL MIX 2T is a lubricant specially formulated to completely protect the engine of modern motorcycles. Dilution ratio 1:25 - 1:50.

## Operation Characteristics

- Resistance to wear
- Excellent smoke emission control
- Excellent deposit control

## Specifications, Approvals, Recommendations

JASO FB, ISO-L-EGB

## Typical Physical Characteristics

	ASTM	MIX 2T
<b>SPECIFIC GRAVITY (kg/l)</b>	D 1298	0,885
<b>VISCOSITY AT 40°C (cSt)</b>	D 445	57,3
<b>VISCOSITY AT 100°C (cSt)</b>	D 445	9
<b>VISCOSITY INDEX</b>	D 2270	136
<b>FLASH POINT (°C) min.</b>	D 92	85
<b>POUR POINT (°C)</b>	D 97	-30

*These are typical values. Small variation should be expected for future productions / blendings.*

## Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.