

MOTO syn mix +

Description

Premium quality, semi-synthetic two-stroke engine oil designed for use in high demand engines. It offers smoke reduction, deposit control and exhaust blocking prevention. It meets the demanding Husqvarna HVA 346 and 372 tests.

Application

ROVEL SYN MIX PLUS is recommended for 2-stroke racing motorbikes, chainsaws and lawn cutters. Dilution ratio 1:50

Operation Characteristics

- Protect metal parts from corrosion and rust.
- Resistance to oxidation at high temperatures
- High resistance to wear
- Excellent deposit control
- Very good emission control

Specifications, Approvals, Recommendations

API TC, JASO FD, TISI, ISO-L-EGD, Husqvarna HVA 346 & 372

Typical Physical Characteristics

	ASTM	SYN MIX PLUS
SPECIFIC GRAVITY (kg/lt)	D 1298	0,870
VISCOSITY AT 40°C (cSt)	D 445	48,6
VISCOSITY AT 100°C (cSt)	D 445	8
VISCOSITY INDEX	D 2270	136
FLASH POINT (°C) min.	D 92	85
POUR POINT (°C)	D 97	-36

These are typical values. Small variation should be expected for future productions / blendings.

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.