

# MOTO syn 10W40

## Description

Premium synthetic four-stroke motorcycle oil, designed for high output engines. It offers optimum clutch performance, high lubricity and gearbox wear protection.

## Application

MOTO SYN 10W-40 is recommended for all types of 4-stroke motorcycle engines and especially the high displacement/high output motors. It meets the severe requirements of traffic and long-distance runs, providing hydrodynamic lubrication and superior engine cleanliness.

## Operation Characteristics

- High oxidation resistance
- Excellent cold start and rapid circulation of lubricant
- Excellent protection against wear and flawless lubrication
- Reduced fuel and lubricant consumption
- High oxidation resistance
- Anti-clutch slippage, disk protection

## Specifications, Approvals, Recommendations

API SL, JASO MA2

## Typical Physical Characteristics

	ASTM	10W-40
<b>SPECIFIC GRAVITY (kg/l)</b>	D 1298	0,875
<b>VISCOSITY AT 40°C (cSt)</b>	D 445	93
<b>VISCOSITY AT 100°C (cSt)</b>	D 445	14,2
<b>VISCOSITY INDEX</b>	D 2270	157
<b>FLASH POINT (°C) min.</b>	D 92	>220
<b>POUR POINT (°C)</b>	D 97	-36
<b>TBN</b>	D 2896	6,6

*These are typical values. Small variation should be expected for future productions / blendings.*

## Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.