

PRIMO 20W50

Description

Multi grade engine oil for passenger cars and light commercial vehicles. It offers anti wear protection, engine cleansing and low service cost.

Application

PRIMO 20W-50 is an economy lubricant designed for wear protection. It is suitable for all seasons and medium drain intervals in gasoline and diesel engines of passenger cars and light duty trucks.

Operation Characteristics

- Reliable operation and efficiency in PCMO engines
- Protection against creating combustion residues
- Strong oil film for engine wear protection.
- Reduced fuel consumption and reduced emissions
- Good oxidation performance.
- Compatible with all gaskets and sealants

Specifications, Approvals, Recommendations

API SJ/CF

Typical Physical Characteristics

	ASTM	20W-50
SPECIFIC GRAVITY (kg/l)	D 1298	0,885
VISCOSITY AT 40°C (cSt)	D 445	165,0
VISCOSITY AT 100°C (cSt)	D 445	18,5
VISCOSITY INDEX	D 2270	126
TBN	D 2896	8
FLASH POINT (°C) min.	D 92	248
POUR POINT (°C)	D 97	-24

These are typical values. Small variation should be expected for future productions / blendings.

Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.