

# SHIFT MTF 75W80

## Description

Synthetic multigrade lubricant for passenger car gearboxes. It is produced with new technology additives and is recommended as service fill gearbox fluid.

## Application

Shift MTF 75W80 is designed to work as a service fill fluid in synchromesh gear boxes of both European and Asian vehicles.

## Operation Characteristics

- Reliable operation under high loads in manual gearboxes
- Prevents reliably from wear, creating sludge and oxidation
- Reliable operation in all temperatures
- Superior bearing and gear protection
- Excellent foaming properties
- Excellent performance at low temperatures.

## Specifications, Approvals, Recommendations

API GL-4. SFU: Mercedes-Benz, VW group, Fiat, Ford, Honda, Hyundai, Nissan, Peugeot, Citroen, Renault, Rover, Jeep, Opel, Toyota, Porsche, Suzuki, Volvo.

## Typical Physical Characteristics

	ASTM	75W-80
<b>SPECIFIC GRAVITY (kg/l)</b>	D 1298	0,86
<b>VISCOSITY AT 40°C (cSt)</b>	D 445	54
<b>VISCOSITY AT 100°C (cSt)</b>	D 445	9,8
<b>VISCOSITY INDEX</b>	D 2270	170
<b>FLASH POINT (°C) min.</b>	D 92	200
<b>POUR POINT (°C)</b>	D 97	-45

*These are typical values. Small variation should be expected for future productions / blendings.*

## Health, Safety and Environmental Protection

It is unlikely to cause any significant problem to the health or safety of the user when used properly, according to the typical handling of lubricating and usual personal hygiene practices. The used lubricants must be recycled in accordance with applicable legislation and placed in approved collection points. Do not discharge into drains, soil or water / sea. Always follow the instructions of the safety data sheet.